

Floorstander - CRITERION TAL 130



Two 19 cm cast-chassis bass units with extra-hard laminated cones drive the transmission line and endow the speaker with enormous pressure in the low bass. As with the larger models, the mid-range/high-frequency assembly is mounted on a de-coupled baffle, and consists of a 13 cm cast mid-range driver with aluminium cone and the new 26 mm woven treble unit. This is the key to the airy, dynamic overall sound so typical of the new Criterion series. As with the other models all three frequency ranges can be varied to the extent of about +/- 2 dB. The cross-over units are separate for the mid-range/high-frequency and bass areas, and this makes it a straight-forward matter to set up bi-amping or bi-wiring.

Specifications

<i>Principle</i>	3 – way – transmission line floor-stander
<i>Nominal power rating</i>	130 Watts
<i>Music power rating</i>	170 Watts
<i>Impedance</i>	4 Ohms
<i>Frequency response</i>	32 – 30000 Hz
<i>Sensitivity 90 dB/1 m</i>	2,2 Watst
<i>Bass drive unit</i>	2 x 190 mm
<i>Mid-range drive unit</i>	1 x 130 mm
<i>High-frequency drive unit</i>	1 x 26 mm
<i>Crossover unit, type</i>	FSR
<i>Crossover frequencies</i>	250 Hz, 2500 Hz
<i>Bi-amping</i>	yes
<i>Dimensions H x W x D</i>	100 x 23 x 36 cm
<i>Weight</i>	26 kg
<i>Colours</i>	Natural beech, natural alder, natural mable, white lacquer rubbed, black lacquer rubbed, silver lacquer rubbed
	Variable HF, MR, B

We reserve the right to alter technical specifications