

Floorstander - CRITERION TAL 160



TAL 160 speakers have a fine detail resolution, dynamics and imaging power previously unknown. With an extreme bass response which it would be an understatement to describe as a miracle. With a completely de-coupled mid-range/high-frequency baffle bearing two 17 cm cast drive units with feather-light aluminium cones and a super high-frequency dome with woven membrane and supplementary heat-sink.

With a transmission line driven by two 26 cm cast magnesium bass units with exceptionally hard carbon cones. (These drive units have extremely long-throw coils and can therefore transmit even the lowest frequencies at very high levels with great clarity.) The speakers also feature two separate FSR cross-over units for the mid-range/high-frequency and bass regions, themselves mounted on vibration-absorbent silentbloks. They even feature level switches for the treble, mid-range and bass regions, 50 mm thick laminated side walls, an extremely stiff internal housing and a separate mid-range chamber.

Specifications

<i>Principle</i>	3 – way – transmission line floor-stander
<i>Nominal power rating</i>	180 Watts
<i>Music power rating</i>	260 Watts
<i>Impedance</i>	4 Ohms
<i>Frequency response</i>	28 – 30000 Hz
<i>Sensitivity 90 dB/1 m</i>	2,0 Watst
<i>Bass drive unit</i>	2 x 260 mm
<i>Mid-range drive unit</i>	2 x 170 mm
<i>High-frequency drive unit</i>	1 x 26 mm
<i>Crossover unit, type</i>	FSR
<i>Crossover frequencies</i>	160 Hz, 2400 Hz
<i>Bi-amping</i>	yes
<i>Dimensions H x W x D</i>	130 x 33 x 46 cm
<i>Weight</i>	61 kg
<i>Colours</i>	Natural beech, natural alder, white lacquer rubbed, black lacquer rubbed, silver lacquer rubbed,
	Variable HF, MR, B

We reserve the right to alter technical specifications