

Floorstander - CRITERION TAL 110



The TAL 110 is the smallest of the Criterion floor-standers, and boasts internal components of outstanding quality. As a result a sound image worthy of the Criterion name is produced effortlessly even from this super-slim cabinet. The transmission line is driven by two 17 cm bass units. In the mid-range/high-frequency area the 26 mm woven dome and 13 cm aluminium mid-range drive unit provide a typically free, airy and dynamic sound, harmonising perfectly with the precision and liveliness of the bass range. Genuine bi-amping and bi-wiring are simple to set up; the only feature we have omitted is the separate control over the frequency ranges

Specifications

| | |
|----------------------------------|--|
| <i>Principle</i> | 3 – way – transmission line floor-stander |
| <i>Nominal power rating</i> | 110 Watts |
| <i>Music power rating</i> | 150 Watts |
| <i>Impedance</i> | 4 Ohms |
| <i>Frequency response</i> | 35 – 30000 Hz |
| <i>Sensitivity 90 dB/1 m</i> | 2,3 Watst |
| <i>Bass drive unit</i> | 2 x 170 mm |
| <i>Mid-range drive unit</i> | 1 x 130 mm |
| <i>High-frequency drive unit</i> | 1 x 26 mm |
| <i>Crossover unit, type</i> | FSR |
| <i>Crossover frequencies</i> | 250 Hz, 2500 Hz |
| <i>Bi-amping</i> | yes |
| <i>Dimensions H x W x D</i> | 90 x 20 x 33 cm |
| <i>Weight</i> | 21 kg |
| <i>Colours</i> | Natural beech, natural alder, natural mable, white lacquer rubbed, black lacquer rubbed, silver lacquer rubbed |

We reserve the right to alter technical specifications