



PA 1260 R – INTEGRATED AMPLIFIER

PA 1260 R audiophile integrated amplifier. Building small, compact integrated amplifiers with superior sound quality is a great art – an art which T+A has mastered like no other company. Like its superbly reviewed predecessor, the PA 1230 R, the PA 1260 R is also assembled from the brilliant components, circuit boards and technologies developed for our pre-amplifiers and power amplifiers. We sanction no compromises, and for this reason the machine achieves exactly the same level of sound quality as these individual modules, and although it offers slightly less output power than the A 1560, it is still capable of delivering a lavish 300 Watts continuous power into 4 Ohms. Even large and critical loudspeakers are tamed and controlled effortlessly by this amplifier. Seven line-level inputs, two tape outputs and one pre-amplifier output make this all-rounder the fabulous heart of a compact High-End system with exceptional sound.



Specifications

Pre-amplifier stage

Frequency response (+0 -3 dB) 0,5 Hz – 400 KHz

Signal noise ratio

High-level 7 x 107 / 109 dB

Phono MM (optional) 82 / 86 dB

Phono MC (optional) 78 / 82 dB

Subsonic Filter 14 Hz

Total harmonic distortion < 0,001 %

Intermodulation < 0,001 %

Channel separation > 90 dB

Input sensitivity nominal

High-level 250 mV / 20 kOhm

Phono MM (optional) 1 – 5 mV / 16 capacitances

Phono MC (optional) 60 – 1000 µV / 16 impedances

Phono module replaced one high-level input

Outputs

Head phone 50 Ohms

2 x Tape 250 mV eff / 100 Ohms

PRE out RCA nominal 1 V eff

maximal 9,5 V eff

Impedance 22 Ohms

PRE out XLR nominal 1,45 V eff

maximal 19,6 V eff

Impedance 22 Ohm

Surround interface (TASI) built in

Output stage

Nominal output per channel into 8 Ohms 100 Watts

Both channels simultaneously into 4 Ohms 150 Watts

Peak output into 8 Ohms 150 Watts

Peak output into 4 Ohms	290 Watts
Power bandwidth	1 Hz – 300 kHz
Frequency response +0 – 3 dB	1 Hz – 400 kHz
Slew rate	60 V/ μ s
Damping factor	>500
Signal:noise ratio	>110 dB
Total harmonic distortion	<0,002 %
<i>Reservoir capacity</i>	50000 μ F
<i>Mains 110 V/60 Hz or 220/240 V/50 Hz</i>	300 VA
<i>Dimensions (H x W x D)</i>	7,5 x 44 x 39 cm
<i>Weight</i>	7 kg
<i>Finishes</i>	silver aluminium, black
<i>Remote control</i>	incl. FM 100 R
<i>we reserve the right to alter technical specifications</i>	